


FlexiPanels[®] Advanced HMI



FP4 Series




FP4 Advanced series offers a powerful, feature rich and versatile HMI product range that provides a perfect solution for complex application needs. A powerful combination of FlexiSoft configuration software and new FlexiSoft runtime gives a perfect balance of ease of configuration and efficient performance.

MODEL COMPARISON

Model	FP40	43 Series	eries FP4070 Series FP4101 Series		01 Series	FP4121 Series		FP4151 Series			
Part	FP4043T	FP4043TN	FP4070	T FP4070TN	FP4101 ⁻	FP4101TN	FP4121T	FP4121TN	FP4151T	FP4151TN	
					Display						
Size	4.3" WQV	GA Color TFT	7" WVG	7" WVGA Color TFT		10.1" WSVGA Color TFT		12.1" SVGA Color TFT		15" XGA Color TFT	
Resolution	n 480 x 272		800 x 480		1024 x 600		800 x 600		1024 x 768		
Touch	Analog Resistive		Analog Resistive		Analog Resistive		Analog Resistive		Analog Resistive		
				CP	U and Po	ower	·		·		
CPU	32-bit RISC processor		32-bit RISC processor		32-bit RISC processor		32-bit RISC processor		32-bit RISC processor		
eMMC	4 GB		4 GB		4 GB		4 GB		4 GB		
RAM	512 MB		512 MB		512 MB		512 MB		512 MB		
Power Supply	24 VDC (±15%)		24 VDC (±15%)		24 VDC (±15%)		24 VDC (±15%)		24 VDC (±15%)		
Isolation	Yes		Yes		Yes		Yes		Yes		
RTC	Built-in		Built-in		Built-in		Built-in		Built-in		
				Cor	mmunica	tion					
Serial	2X RS232 / RS485 [#]		2x RS232 / RS485		2x RS232 / RS485		2x RS232 / RS485		2x RS232 / RS485		
USB Device	1x micro 2.0		1x micro 2.0		1x micro 2.0		1x micro 2.0		1x micro 2.0		
USB Host	1x 2.0		1x 2.0		1x 2.0		1x 2.0		1x 2.0		
Ethernet	NA	1x 10/100 Mbps	NA	1x 10/100 Mbps	NA	1x 10/100 Mbps	NA	1x 10/100 Mbps	NA	1x 10/100 Mbps	
SD Card Slot	NA	1x microSD HC	NA	1x microSD HC	NA	1x microSD HC	NA	1x microSD HC	NA	1x microSD HC	
				Environ	ment & A	pprovals					
Operating Temperature	-10~60°C*		-10~60°C*		-10~60°C*		-10~60°C*		-10~60°C*		
Storage Temperature	-20~85°C		-20~85°C		-20~85°C		-20~85°C		-20~85°C		
Humidity	10~95% non condensing		10~95% non condensing		10~95% non condensing		10~95% non condensing		10~95% non condensing		
Shock	25g, 11ms, 6 shocks per axis, Total 18 shocks (X, Y, Z)		25g, 11ms, 6 shocks per axis, Total 18 shocks (X, Y, Z)		25g, 11ms, 6 shocks per axis, Total 18 shocks (X, Y, Z)		25g, 11ms, 6 shocks per axis, Total 18 shocks (X, Y, Z)		25g, 11ms, 6 shocks per axis, Total 18 shocks (X, Y, Z)		
Vibration	5~150 Hz, 3g peak, (X, Y, Z)		5~150 Hz, 3g peak, (X, Y, Z)		5~150 Hz, 3g peak, (X, Y, Z)		5~150 Hz, 3g peak, (X, Y, Z)		5~150 Hz, 3g peak, (X, Y, Z)		
Protection	IP66 for front panel mounting		IP66 for front panel mounting		IP66 for front panel mounting		IP66 for front panel mounting		IP66 for front panel mounting		
Approvals	Approvals CE, UL Class I Div 2		CE, UL Class I Div 2		CE, UL Class I Div 2		CE, UL Class I Div 2		CE, UL Class I Div 2		

*Note: For UL Operating Temperature range is 0-50°C. # FP4043 support One DB9 port that supports RS232 and RS485 levels on different pins. "Y" type cable can be used for separate RS232 and RS485 levels simultaneously.

APPLICATION EXAMPLE



Objects



FP4 advanced series offers variety of objects like buttons, bar graphs, lamps, meters, multilingual text, calendar, clock etc. along with data display / data entry and other static objects. The objects support powerful animation and gradient effects.

Datalogging and recipe

FP4 supports powerful data logging with the option of using internal memory or external memory for logging the data. It also supports powerful recipe wizard.

Trend and XY Plot






FP4 supports powerful graphical representation of tag against the real time. It also supports graphical representation of historical data.

Alarm

FP4 supports real time as well as historical alarms. Using Alarm object, user can visualize generated Alarm with system. For better Visualization multiple fonts, colours can be used for indication.





Connectivity

FP4 provides connectivity over USB, Ethernet and Serial ports. User can download and upload the application to/from the device and monitor logic and data.

FTP

FP4 supports FTP Host & Client. This feature is provided to transfer logged data from an external device to their FTP server.





4.3" T : No Ethernet and SD card slot
7" TN : Supports Ethernet and SD card slot
10.1"
15"


SUPPORTED PROTOCOLS

Modbus RTU (Unit as Master)
Modbus RTU (Unit as Slave)
Modbus/TCP Master (Client)
Modbus ASCII (Unit as Master)
Universal Ethernet Driver (ASCII)
Universal Serial Driver (ASCII)

Siemens Profinet PLCs
FlexiLogics Master Driver
FlexiLogics Slave Driver
Panasonic FP Series
Fatek PLCs
Delta PLCs

Note:Presently FP4 Series HMIs Support above Communication Protocols. We plan to support more protocols soon. Please contact factory regarding more information about it.

DIMENSIONS



(Preliminary Datasheet. Specifications subject to change without prior notice. DS-FP-4-Rev.G)